



WATERTIGHT BREAKAWAY CONNECTORS

AP- and AJ- Series Connectors

TECHNICAL SPECIFICATIONS						
Shell:	Aluminum					
Plating:	Black Anodize (standard); Black Chrome (shielded)					
Insert:	Thermoset Plastic					
Contacts:	Gold-plated Brass (Jacks) / Gold-plated BeCu (Plugs)					
Mating:	Axial push-pull motion					
Engagement Force:	≤ 14 lbs					
Disengagement Force:	8-12 lbs. (Standard) 5-12 lbs. (Miniature)					
Mating Cycles:	5000 (Standard) 3000 (Miniature					
Temperature:	-55°C to +85°C					
Contact Current Capacity:	2 amps maximum					
Contact Resistance:	≤ 150 mV					

Amphenol NEXUS Technologies is the leader in watertight, breakaway connectors designed to meet severe environmental conditions. Our connectors, which are watertight in up to 6 feet of water, have molded-on wiping-action contacts that provide a self-cleaning feature and eliminate issues with pin/socket open contacts.

The 7-Pin and 10-Pin connectors are designed for multiple cable diameters, are available in shielded versions, and can include either solder-type contacts of insulation-piercing contacts, which are field replaceable.

Many of the 7- and 10-pin Connectors also come in a miniature versions that is 50% smaller than the standard connector. All standard connector options are also available in the miniaturized versions.

APPLICATIONS:

- C4I Systems
- Military Vehicles
- Commercial Aircraft
- Telecommunications Equipment
- Missiles and Ordnance
- Medical Equipment
- Commercial / Industrial Equipment

WATERPROOF BREAKAWAY CONNECTORS:



AP-107

Connector Type: Plug Number of Contacts: 7 **Contact Type:** Insulation Piercing Rear Accessory: None



AJ-107

Connector Type: Jack Number of Contacts: 7 **Contact Type:** Insulation Piercing Rear Accessory: None



AP-107BRS

Connector Type: Plug, Shielded Number of Contacts: 7 **Contact Type:** Solder Rear Accessory:

Wire Strain Relief



AJ-107BRS

Connector Type: Jack. Shielded Number of Contacts: 7 **Contact Type:** Solder **Rear Accessory:**

Wire Strain Relief



AP-107PM

Connector Type: Jack, Front Mount Panel Mount **Number of Contacts: 7 Contact Type:** Solder Rear Accessory: None



AJ-107PM

Connector Type: Plug, Front Mount Panel Mount **Number of Contacts: 7 Contact Type:** Solder Rear Accessory: None



AP-1170M

Connector Type: Plug, Miniature Number of Contacts: 7 **Contact Type:** Solder Rear Accessory: Overmold



AJ-1170M

Connector Type: Jack, Miniature Number of Contacts: 7 **Contact Type:** Solder Rear Accessory: Overmold



AP-117BR

Connector Type: Plug, Miniature Number of Contacts: 7 Contact Type: Solder Rear Accessory: Wire Strain Relief

(.148 max)



AJ-117BR

Connector Type: Jack, Miniature **Number of Contacts: 7** Contact Type: Solder **Rear Accessory:** Wire Strain Relief (.148 max)



AJ-117PM

Connector Type: Front Panel-Mount Jack, Miniature Number of Contacts: 7 **Contact Type:** Solder

Rear Accessory: None



AP-110BRXL

Connector Type: Plug, Miniature Number of Contacts: 10 **Contact Type:** Solder Rear Accessory: Wire Strain Relief (.250 max)



AJ-110BRXL

Connector Type: Jack, Miniature **Number of Contacts: 10 Contact Type:** Solder Rear Accessory: Wire Strain Relief (.250 max)



AMPHENOL NEXUS TECHNOLOGIES

WATERPROOF BREAKAWAY CONNECTORS CONTINUED:

NEXUS Part Number	Connector Type	Number of Contacts	Contact Type	Rear Accessory		
AP-107BR*	Plug	7	Solder	Wire Strain Relief		
AJ-107BR*	Jack	7	Solder	Wire Strain Relief		
AP-117BRXL*	Plug, Miniature	7	Solder	Wire Strain Relief (.250 max)		
AJ-117BRXL*	Jack, Miniature	7	Solder	Wire Strain Relief (.250 max)		
AP-107DR*	Plug	7	Insulation Piercing	Overmold Cap		
AJ-107DR*	Jack	7	Insulation Piercing	Overmold Cap		
AP-107DRS*	Plug, Shielded	7	Insulation Piercing	Overmold Cap		
AJ-107DRS*	Jack, Shielded	7	Insulation Piercing	Overmold Cap		
AP-117LR-AL*	Plug, Miniature w/Threaded Locking Ring	7	Solder	Wire Strain Relief (.250 max)		
AJ-117LR-AL*	Jack, Miniature w/Threaded Locking Ring	7	Solder	Wire Strain Relief (.250 max)		
AP-117PLR*	Plug, Miniature w/Threaded Locking Ring	7	Solder	Overmold		
AJ-117PLR*	Jack, Miniature w/Threaded Locking Ring	7	Solder	Overmold		
AJ-117PMDC*	Jack, Rear Panel-Mount, Miniature	7	Solder	None		
AP-1100M*	Plug, Miniature	10	Solder	Overmold		
AJ-1100M*	Jack, Miniature	10	Solder	Overmold		
AP-1100MS*	Plug, Miniature, Shielded	10	Solder	Overmold		
AJ-1100MS*	Jack, Miniature, Shielded	10	Solder	Overmold		

*Image not shown

CABLE HARNESS INFORMATION:

NEXUS Part Number	Cable I	Holder	Cable Seal	Cable (6 Conductor) with Shield			
	Part Number	Figure Below	Cable Seal	Cable (o Conductor) with Sillera			
AP-107XL AJ-107XL	AP-107-3BXL AJ-107-3GXL	А	AP-107-27	.275 D/A .060 D/A			
AP-107XLS AJ-107XLS	AP-107-3BXLS AJ-107-3BXLS	В	AP-107-27	OVER INSULATION MIL-C-3885			
AP-107 AJ-107	AP-107-3B AJ-107-3G	С	Customer molds strain relief, then uses AP-107-27	.172 D/A .039 D/A			
AP-107A AJ-107A	AP-107-3B AJ-107-3G	С	AP-107-31	OVER INSULATION MIL-C-55668			

WATERTIGHT BREAKAWAY CONNECTOR MATING CHART:

		JACKS													
	MATES WITH	AJ- 107	AJ- 107BR	AJ- 107BRS	AJ- 107DR	AJ- 107DRS	AJ- 1100M	AJ- 1100MS	AJ- 117BR	AJ- 117BRXL	AJ- 117LRAL	AJ- 117OM	AJ- 117PRL	AJ- 117PM	AJ- 117PMDC
	AP-107	Х	Χ	X	Χ	Х									
	AP-107BR	Χ	X	Χ	Χ	Χ									
	AP-107BRS	Χ	X	X	X	Χ									
	AP-107DR	Χ	Χ	X	Χ	X									
	AP-107DRS	Χ	Χ	X	Χ	Χ									
G S	AP-1100M						Χ	Χ							
PLUGS	AP-1100MS						Χ	X							
₫	AP-117BR								Χ	Χ		X		Χ	Χ
	AP-117BRXL								Х	Χ				Χ	Χ
	AP-117LR-AL										Χ				
	AP-1170M											Χ		Χ	X
	AP-117PLR												Χ		