



Solid-state indicators provide system information

FEATURES

- Environmentally sealed
- Rugged packaging
- Pinpoint or wide-angle viewing area
- EMI shielding available
- Anti-reflective coating optional
- Panel mount & rear mount designs
- Models available to meet NVIS and MIL-Spec requirements
- Custom designs



FIGURE 1



FIGURE 2



FIGURE 3



FIGURE 4



FIGURE 5



FIGURE 6



FIGURE 7



FIGURE 8



FIGURE 9



FIGURE 10



FIGURE 11



FIGURE 12



FIGURE 13



FIGURE 14



FIGURE 15

| Fig. No. | Models | Environ Sealed | Panel Seal | Rear Mount | Panel Mount | Internal Resistors | Wide Operating Voltage | Night Vision | Infrared Secure | High Brightness | EMI Shielded | Tri-Color Bi-Color LED | Page No. |
|----------|---------------------------------|----------------|------------|------------|-------------|--------------------|------------------------|--------------|-----------------|-----------------|--------------|------------------------|----------|
| 1 | ML1600 ^② | • | | | • | • | | | | | | | 32 |
| 2 | ML1610 | • | • | | • | | | | | | | | 32 |
| 3 | ML1618 ^④ | • | | | • | | | | • | | | | 34 |
| 4 | ML1619 ^{④⑨} | • | | | • | | | | • | | • | | 36 |
| 5 | MLD1619 ^{④⑤} | • | | | • | | | | • | | • | | 38 |
| 6/7 | ML1620/ML1630 ^② | • | • | | • | • | | | | | • | | 40 |
| 6/7 | ML1620-S/ML1630-S | • | • | | • | | | | | | • | | 42 |
| 6/7 | ML1622/ML1632 ^② | • | • | | • | • | | | | | • | B | 44 |
| 8/7 | ML1623-S/ML1633-S ^{①②} | • | • | | • | • | | | | | • | B | 46 |
| 9 | ML1631 ^⑧ | • | • | • | | | | | | | • | T | 48 |
| 10 | ML1634 | • | • | • | | | | | | | • | B | 50 |
| 11 | ML1635 ^① | • | • | • | | | | | | | • | B | 52 |
| 10 | ML1636 ^② | • | • | • | | • | | | | | • | | 54 |
| 10 | ML1636-U | • | • | • | | | | | | • | • | | 56 |
| 10 | ML1638 ^③ | • | • | • | | | | • | | | • | | 58 |
| 11 | ML1638 Bi-Color ^{①③} | • | • | • | | | | • | | | • | B | 60 |
| 12 | ML1640 ^⑦ | • | • | | • | | | | | | • | | 62 |
| 4 | ML1662 ^③ | • | • | | • | | | • | | | • | | 64 |
| 13 | ML2030E ^⑥ | • | • | | • | | | | | | • | | 66 |
| 14 | ML2031 ^⑧ | • | • | | • | | | | | | • | T | 68 |
| 13 | ML2038E ^③ | • | • | | • | | | • | | | • | | 70 |
| 15 | ML4036 | • | • | • | | | • | | | • | • | | 72 |

Notes: ^① 3-Leaded ^② Internal Resistors for 5VDC to 28VDC usage. ^③ MIL-L-85762A ^④ CECOM Secure Lighting ^⑤ Dimmable Filter feature ^⑥ DESC Drawing 85122 ^⑦ DESC Drawing 85122 ^⑧ 4-Leaded ^⑨ DESC Drawing 87019

This page consists of basic marketing information that is not defined as technical data under EAR Part 772.