

**Terminal Selection Guide**

Your Application's Parameters					Rebling Terminal Selection Guide				Accessories				
Rated Current	Your Panel	Your Panel Thickness	Desired Panel Mounting	Connector Plating	Style	Insulator Color	P/N for bagged Kit	Advantages over other Styles	O-ring	Gasket	Flexible Cover	Long Rigid Cover	Short Rigid Cover
100 amps	Plastic or Metal	0.025 → 0.157" 0,64 → 4,0 mm	3 circular holes	Ni-plated Brass	TFT	Black Red Blue	TFT-P-B TFT-P-R TFT-P-E	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	812A1925	-	815A1927-B (BLK) 815A1927-R (RED) 815A1927-E (BLU)	814A1926-B (BLK) 814A1926-R (RED) 814A1926-E (BLU)	-
250 amps	Plastic	0.025 → 0.220" 0,64 → 5,59 mm	3 circular holes	Ni-plated Brass	SFT	Black Red Blue	SFT-P-B SFT-P-R SFT-P-E	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	716A1814	713A1806-B (BLK) 713A1806-R (RED) 713A1806-E (BLU)	698A1789-L-B (BLK) 698A1789-L-R (RED) 698A1789-L-E (BLU)	698A1789-S-B (BLK) 698A1789-S-R (RED) 698A1789-S-E (BLU)
		0.230 → 0.660" 5,84 → 16,76 mm	1 double-D hole	Ni-plated Brass	LFT	Black Red Blue	LFT-P-B LFT-P-R LFT-P-E	Smallest Footprint, Lowest Cost Simplest Environmental Seal	700A1799	-			
			3 circular holes	Ni-plated Brass	SFT	Black Red Blue	SFT-P-B SFT-P-R SFT-P-E	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	716A1814			
	Metal	0.025 → 0.100" 0,64 → 2,54 mm	3 circular holes	Ni-plated Brass	SFT	Black Red Blue	SFT-P-B SFT-P-R SFT-P-E	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	716A1814			
		0.110 → 0.660" 2,80 → 16,76 mm	1 double-D hole	Ni-plated Brass	LFT	Black Red Blue	LFT-P-B LFT-P-R LFT-P-E	Smallest Footprint, Lowest Cost Simplest Environmental Seal	700A1799	-			
			3 circular holes	Ni-plated Brass	SFT	Black Red Blue	SFT-P-B SFT-P-R SFT-P-E	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	716A1814			
500 amps	Plastic or Metal	0.025 → 0.660" 0,64 → 16,76 mm	3 circular holes	Ni-plated Brass	MFT	Black Red Blue	MFT-P-B MFT-P-R MFT-P-E	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	716A1815			
750 amps	Plastic	0.025 → 0.180"	3 circular holes	Ni-plated Brass	XFT	Black Red	XFT-P-B XFT-P-R	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	720A1817	639A1830-B (BLK) 639A1830-R (RED)	-	
	Plastic	0.190 → 0.550" 4,83 → 13,97 mm	1 double-D hole	Ni-plated Brass	BFT	Black Red	BFT-P-B BFT-P-R	Smallest Footprint, Lowest Cost Simplest Environmental Seal		651A1811		648A1758 (BLK) 648A1779 (RED)	
			3 circular holes	Ni-plated Brass	XFT	Black Red	XFT-P-B XFT-P-R	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		720A1817		-	
	Metal	0.025 → 0.070"	3 circular holes	Ni-plated Brass	XFT	Black Red	XFT-P-B XFT-P-R	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		720A1817			
			0.080 → 0.550" 2,04 → 13,97 mm	1 double-D hole	Ni-plated Brass	BFT	Black Red	BFT-P-B BFT-P-R		Smallest Footprint, Lowest Cost Simplest Environmental Seal		651A1811	648A1758 (BLK) 648A1779 (RED)
				3 circular holes	Ni-plated Brass	XFT	Black Red	XFT-P-B XFT-P-R		Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		720A1817	-
1000 amps	Plastic	0.025 → 0.180"	3 circular holes	Ni-plated Copper	XFT	Black Red	XFT-N-B XFT-N-R	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill	-	720A1817	639A1830-B (BLK) 639A1830-R (RED)	-	
		0.190 → 0.550" 4,83 → 13,97 mm	1 double-D hole	Ni-plated Copper	BFT	Black Red	BFT-N-B BFT-N-R	Smallest Footprint, Lowest Cost Simplest Environmental Seal		651A1811		648A1758 (BLK) 648A1779 (RED)	
			3 circular holes	Ni-plated Copper	XFT	Black Red	XFT-N-B XFT-N-R	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		720A1817		-	
	Metal	0.025 → 0.070"	3 circular holes	Ni-plated Copper	XFT	Black Red	XFT-N-B XFT-N-R	Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		720A1817			
			0.080 → 0.550" 2,04 → 13,97 mm	1 double-D hole	Ni-plated Copper	BFT	Black Red	BFT-N-B BFT-N-R		Smallest Footprint, Lowest Cost Simplest Environmental Seal		651A1811	648A1758 (BLK) 648A1779 (RED)
				3 circular holes	Ni-plated Copper	XFT	Black Red	XFT-N-B XFT-N-R		Can be mounted on very thin or weak panels Mounting holes can be made with a hand drill		720A1817	-